

MISCELLANEOUS NOTICES AND REPORTS ON GEOTHERMAL WELLS
(Submit in triplicate)

This is a combined form; use only portions pertinent to your needs.

To comply with rules and regulations adopted pursuant to ORS 522 (Chapter 776, OL 1971)

Notices

Reports

Indicate nature of notice by checking below:

Indicate nature of report by checking below:

Notice of intention to plug well		Report on plugging well (use form 6-6/72)	
Notice of intention to make formation test		Report on making formation test	
Notice of intention to make production test		Report on making production test	
Notice of intention to abandon well	X	Report on abandoning well	
Notice of intention to test casing shut-off		Report on testing casing shut-off	
Notice of intention to redrill or deepen well		Report on redrilling or deepening well	
Notice of intention to shoot or chemically treat well		Report on shooting or chemically treating well	
Notice of intention to complete well		Report on completion of well	

Submit notices in triplicate before the work specified is to begin. A copy will be returned to the sender on which will be given the approval, with any modifications considered advisable, or the rejection by the Department or agent, of the plan submitted.

Submit reports in triplicate within 30 days after the work specified is completed. For abandonment work a report must be made within 5 days.

Portland, Oregon, October 3 1974

Department of Geology and Mineral Industries
Portland, Oregon 97201

Following is a report on the work done and the results obtained at the MAGMA ENERGY, INC.
notice of intention to do certain work as described below Company or Operator

Lease Magma - La Grande Well No. 1 in NW4 NW4

of sec. 9, T. 4 S, R. 39 E, W. B. & M., La Grande field,

Union County. The dates of this work were as follows: 9/24/74 Thru 9/27/74

The present condition of the well:

712' of 13 3/8" - 54.5 - J-55 from Surface to 712' K.B. to GRD. 12'
7 7/8" hole to 2729'

Proposed work or work done:

- 1 - Lay a cement plug 50' below and 50' inside 13 3/8" casing.
- 2 - Lay cement plug 6' below surface and 20' inside of 13 3/8" casing.
- 3 - Cap 13 3/8" casing with 1/2" steel plate 6' below surface.
- 4 - Remove cellar boards and fill cellar in with dirt.
- 5 - Restore drill site to as near its original state as possible.

Approved _____ 19____
except as follows:

DEPT. OF GEOLOGY & MINERAL INDUS.

By _____
Director

MAGMA ENERGY, INC.
Company or Operator
By Edward Zajac V.P. Drilling
Edward Zajac Position

Send communications regarding well to:

Name Edward Zajac

Address 631 So. Witmer Street

Los Angeles, California 90017