Welex PRINT

TEMPERATURE LOG

COMPANY	NORTHWEST GEOTHERMAL CORP.
WELL	OLD MAID FLAT #1
FIELD	NGC (OLD MAID FLAT)
COUNTY	CLACKAMAS
STATE	OREGON
Location	2400' E of W. Line 500' N of S. Line
Sec.	15
Twp	2S
Rge	8E
Other Services	DIGL, CALL, F.E., CPL/GN, D.I.C., SWC
Permanent Datum	G.L.
Elev.	2750'
Log Measured From	K.B. OR 10 Ft. Above Perm. Datum
Drilling Measured From	K.B.
Elev.: K.B.	2760'
D.F.	
G.L.	2750'

Date	8-17-78			
Run No.	ONE			
Depth—Driller	4002'			
Depth—Welex	4000'			
Btm. Log Inter.	4000'			
Top Log Inter.	0			
Casing—Driller	8 5/8 @ 160'	@	@	@
Casing—Welex	162'			
Bit Size	7 7/8			
Type Fluid in Hole	Quik-Gel			
Dens. | Visc.	9.8 | 40	|	|	|
pH | Fluid Loss	10.0 | N.A. ml	| ml	| ml	| ml
Source of Sample	Pit			
R_m @ Meas. Temp.	6.15 @ 60 °F	@ °F	@ °F	@ °F
R_{mf} @ Meas. Temp.	5.92 @ 60 °F	@ °F	@ °F	@ °F
R_{mc} @ Meas. Temp.	6.28 @ 60 °F	@ °F	@ °F	@ °F
Source R_{mf} R_{mc}	M | M	|	|	|
R_m @ BHT	2.22 @ 166 °F	@ °F	@ °F	@ °F
Time Since Circ.	24 Hrs +			
Max. Rec. Temp.	176 °F @ BHT	°F @	°F @	°F @
Equip. | Location	9430 | WNUO	|	|	|
Recorded By	MR. DEVE			
Witnessed By	MR. COLVERT			

Fold Here

Service Ticket No 00698 / Remarks:

Change in Mud Type or Additional Samples		
Date | Sample No.	|	|
Depth—Driller		
Type Fluid in Hole		
Dens. | Visc.	|	|
ph | Fluid Loss	| ml	|
Source of Sample		
R_m @ Meas. Temp.	@ °F	@ °F
R_{mf} @ Meas. Temp.	@ °F	@ °F
R_{mc} @ Meas. Temp.	@ °F	@ °F
Source: R_{mf} | R_{mc}	|	|
R_m @ BHT	2.22 @ 166 °F	@ °F
R_{mf} BHT	2.13 @ 166 °F	@ °F
R_{mc} BHT	2.26 @ 166 °F	@ °F

SCALE CHANGES

Type Log	Depth	Scale Up Hole	Scale Down Hole
Temp	10	30 To 70	60 To 100
	1140	60 To 100	90 To 130
	2410	90 To 130	120 To 160
	3550	120 To 160	150 To 190

EQUIPMENT DATA

Run No.	Tool Type and No.	Pad Type	Tool Position	Other
ONE	Temp 20292		FREE	

Tool Calibrated with Cold Water @ 52°; Hot Water @ 137° outside Temp 62° 68° out Tool read both in and out The same as Termometer read.

Bottom Hole Thermometer read 176°

Welex does not guarantee the accuracy of any interpretation of log data, conversion of log data to physical rock parameters, or recommendations which may be given by Welex personnel or which may appear on the log or in any other form. Any user of such data, interpretations, conversions, or recommendations agrees that Welex is not responsible, except where due to gross negligence or wilful misconduct, for any loss, damages, or expenses resulting from the use thereof.

ONE MINUTE INTERVAL MARK

TEMPERATURE IN DEGREES FAHRENHEIT

30 40 50 60 70

Bottom Hole Termometer Read 176°

BEFORE LOG