

WELL SUMMARY REPORT  
 (Submit in duplicate)

REGISTERED  
 OCT 5 1984

DEPT OF GEOLOGY

W. B. C. M.

Operator Reichhold Energy Corporation Field Mist  
 Well No. Adams 32-34 Sec. 34, T. 7N, R. 5W  
 Location 1550'S & 26'E of N<sup>1</sup>/<sub>2</sub> corn <sup>of</sup> Sec 34 Elevation above sea level 1524.57 feet  
 All depth measurements taken from top of Kelly Bushing, which is 11.2 feet above ground

In compliance with the rules and regulations pursuant to ORS 520 (Chapter 667 OL 1953) the information given herewith is a complete and correct record of the present condition of the well and all work done thereon, so far as can be determined from all available records.

Date October 3, 1984 Signed [Signature]  
 Title Field Operations Supervisor  
 (President, Secretary or Agent)  
 Engineer or Geologist Superintendent

Commenced drilling 8/22/84 Completed drilling 8/30/84 Drilling tools Cable Rotary

Total depth	Plugged depth	GEOLOGICAL MARKERS	DEPTH
<u>3284</u>	<u>180'</u>		
Junk <u>10' of hole</u>			

Commenced producing \_\_\_\_\_ Date \_\_\_\_\_ Flowing/gas lift/pumping (cross out unnecessary words)

	Clean oil bbl per day	Gravity Clean oil	Percent water including emulsion	Gas Mcf per day	Tubing Pressure	Casing Pressure
Initial production						
Production after 30 days						

CASING RECORD (Present Hole)

Size of casing (A.P.L.)	Depth of shoe	Top of casing	Weight of casing	New or second hand	Seamless or Lapweld	Grade of casing	Size of hole drilled	No. of sacks of cement	Depth of cementing if through perforations
<u>8 5/8</u>	<u>412</u>	<u>Surface</u>	<u>24#</u>	<u>New</u>	<u>Seamless</u>	<u>K-55</u>	<u>12 1/2</u>	<u>280</u>	

PERFORATIONS

Size of casing	From	To	Size of perforations	Number of rows	Distance between centers	Method of perforations
	ft.	ft.				
	ft.	ft.				
	ft.	ft.				
	ft.	ft.				