

DI DRIL, INC.  
BAKERSFIELD, CALIF.

JOB NUMBER:

WELL NAME: CER.14-26-64

INRUN SURVEY  
BY MINIMUM CURVATURE

MBAS. DEPTH	VERT. DEPTH	VERT. SECT.	L/R PROP.	INCL	BEARING AZINUTH	COORDINATES LATITUDE	DEPARTURE	D-LEG /100	D-LEG /CL	STATION DISP.	DISPLACEMENT DIRECTION
500.0	500.00	0.00	0.000	00.00	000.00	0.00 N	0.00 E	0.00	0.00	0.00	AT 000.00
556.0	555.99	0.17	0.663	01.40	197.20	0.65 S	0.20 W	2.50	1.40	0.68	AT 197.20
585.3	585.32	0.79	1.413	02.60	158.70	1.62 S	0.07 W	5.93	1.74	1.62	AT 182.36
616.6	616.55	2.56	2.276	04.70	141.30	3.28 S	0.99 E	7.51	2.35	3.43	AT 163.15
646.8	646.53	5.55	3.033	07.10	132.00	5.49 S	3.15 E	8.55	2.58	6.33	AT 150.15
707.3	706.29	14.81	4.408	10.70	128.60	11.50 S	10.32 E	6.01	3.64	15.45	AT 138.09
768.9	766.47	27.76	6.109	13.80	129.30	19.72 S	20.48 E	5.04	3.10	28.43	AT 133.92
798.1	794.69	35.17	6.975	15.80	127.20	24.33 S	26.34 E	7.09	2.07	35.85	AT 132.73
858.7	852.46	53.51	7.810	19.50	121.60	34.62 S	41.54 E	6.71	4.07	54.07	AT 129.81
919.7	909.09	76.09	7.261	24.00	118.90	45.96 S	61.07 E	7.56	4.61	76.43	AT 126.96
981.3	964.65	102.63	6.664	27.10	121.40	59.32 S	84.02 E	5.33	3.28	102.85	AT 125.22
1153.2	1109.70	194.43	3.734	37.60	118.40	104.80 S	163.81 E	6.18	10.62	194.46	AT 122.61
1295.0	1212.21	291.83	-2.695	49.60	117.20	150.23 S	250.21 E	8.48	12.03	291.85	AT 120.98
1386.0	1267.73	363.83	-5.373	55.20	121.40	185.57 S	312.99 E	7.16	6.51	363.86	AT 120.66
1449.0	1302.31	416.47	-5.568	58.20	121.20	212.92 S	357.98 E	4.77	3.00	416.51	AT 120.74
1512.0	1335.56	469.98	-6.324	58.10	120.20	240.24 S	403.99 E	1.36	0.86	470.03	AT 120.74
1543.0	1351.94	496.30	-6.719	58.10	121.10	253.66 S	426.63 E	2.46	0.76	496.34	AT 120.73
1637.0	1399.58	577.28	-8.949	61.00	118.80	294.09 S	496.84 E	3.74	3.51	577.35	AT 120.62
1730.0	1444.52	658.62	-12.585	61.20	119.10	333.50 S	568.08 E	0.35	0.33	658.74	AT 120.42
1824.0	1489.23	741.27	-15.049	62.00	120.50	374.59 S	639.83 E	1.56	1.47	741.42	AT 120.35
1917.0	1533.54	823.03	-14.998	61.10	122.60	417.37 S	709.51 E	2.21	2.05	823.17	AT 120.47
2011.0	1579.11	905.20	-12.431	60.90	124.00	462.50 S	778.22 E	1.32	1.24	905.29	AT 120.72
2104.0	1625.75	985.54	-8.172	58.90	125.10	508.12 S	844.49 E	2.38	2.21	985.57	AT 121.03
2198.0	1674.45	1065.85	-4.398	58.70	123.30	553.31 S	910.99 E	1.65	1.55	1065.86	AT 121.27
2325.0	1740.90	1174.01	-0.641	58.20	123.70	613.05 S	1001.24 E	0.48	0.61	1174.01	AT 121.48
2481.0	1824.27	1305.67	6.456	57.20	125.50	687.91 S	1109.78 E	1.17	1.82	1305.69	AT 121.79
2638.0	1907.81	1438.18	16.869	58.50	126.50	766.04 S	1217.30 E	0.99	1.55	1438.28	AT 122.18
2795.0	1987.97	1572.50	30.266	60.10	127.90	847.67 S	1324.82 E	1.28	2.00	1572.79	AT 122.61
3050.0	2115.85	1791.95	52.909	59.70	126.90	981.66 S	1500.07 E	0.37	0.95	1792.73	AT 123.20

\*\*\*\*\*  
\* THE HORIZONTAL DISPLACEMENT AT THE DEPTH OF \*  
\* 3050.0 FEET EQUALS 1792.73 FEET AT 123.20 \*  
\*\*\*\*\*