

WELL SUMMARY REPORT
(Submit in duplicate)

Operator Linn County Oil Development Co. Field Lebanon Area
Well No. Barr No. 1 Sec. 32, T. 11S, R. 1W, W. B. & M.
Location 262'S & 790'E from the NW cor. Sec. 32 Elevation above sea level 355 Tops feet
All depth measurements taken from top of Kelly Bushings, which is 12 feet above ground

In compliance with the rules and regulations pursuant to ORS 520 (Chapter 667 OL 1953) the information given herewith is a complete and correct record of the present condition of the well and all work done thereon, so far as can be determined from all available records.

Date _____ Signed _____
Engineer or Geologist _____ Superintendent _____ Title _____
(President, Secretary or Agent)

Commenced drilling Oct. 26, 1958 Completed drilling Jan. 11, 1959 Drilling tools Rotary
Total depth 4529' Plugged depth 2180' GEOLOGICAL MARKERS DEPTH
Junk 105' - 3 Drill collars and a bit Eurene Fm. 0-4529'
at (4424-4529)'

Commenced producing Dry hole Date _____ Flowing/gas lift/pumping
(cross out unnecessary words)

	Clean oil bbl. per day	Gravity Clean oil	Percent water including emulsion	Gas Mcf. per day	Tubing Pressure	Casing Pressure
Initial production						
Production after 30 days						

CASING RECORD (Present Hole)

Size of casing (A.P.L.)	Depth of shoe	Top of casing	Weight of casing	New or sec- ond hand	Seamless or Lapweld	Grade of casing	Size of hole drilled	No. of sacks of cement	Depth of cement- ing if through perforations
10 3/4"	440'	surf.	32	New	Smless	H-40	15"	580	Around Shoe
5 1/2"	4422'	surf.	15.5	New	Smless	J-55	7 7/8"	600	Around Shoe

PERFORATIONS

Size of casing	From	To	Size of perforations	Number of rows	Distance between centers	Method of perforations
5 1/2"	4298 ft.	4321 ft.	4 1/2 per foot			Lane Wells - Bullet
5 1/2"	2370 ft.	2371 ft.	4 1/2			Squeeze w/75 sacks
5 1/2"	2233 ft.	2267 ft.	4 1/2 per foot			Attempted squeeze w/10 sacks, too tight, would not take any cement at 1000i
	ft.	ft.				
	ft.	ft.				

10/80