

WELL SUMMARY REPORT  
(Submit in duplicate)

Operator The Texas Co. Field Clatskanie Area  
Well No. Clatskanie 1 NE1/4 Sec. 36, T 7N, R 4W, WM W. B. & M.  
Location 617'N & 1274'W of E1/4 corner Elevation above sea level 271' feet  
All depth measurements taken from top of Kelly Bushing, which is 15.3 feet above ground

In compliance with the rules and regulations pursuant to ORS 520 (Chapter 667 OL 1953) the information given herewith is a complete and correct record of the present condition of the well and all work done thereon, so far as can be determined from all available records.

Date June 19, 1946 Signed W.A. Clark  
T.W. Bell J.H. Puls Title Div. Engr.  
Engineer or Geologist Superintendent (President, Secretary or Agent)

Commenced drilling July 2, 1945 Completed drilling Sept. 28, 1945 Drilling tools Cable Rotary  
Total depth 5650' Plugged depth 0 GEOLOGICAL MARKERS DEPTH  
Junk 973' 4 1/2" dp and drill collars Keasey 0-730'  
4667-5640' U Eoc Marine Seds  
and Volcs 730-5650'

Commenced producing \_\_\_\_\_ Date \_\_\_\_\_ Flowing/gas lift/pumping (cross out unnecessary words)

Initial production  
Production after 30 days

Clean oil bbl. per day	Gravity Clean oil	Percent water including emulsion	Gas Mcf. per day	Tubing Pressure	Casing Pressure

CASING RECORD (Present Hole)

Size of casing (A.P.L.)	Depth of shoe	Top of casing	Weight of casing	New or second hand	Seamless or Lapweld	Grade of casing	Size of hole drilled	No. of sacks of cement	Depth of cementing if through perforations
20"	115'	0	78#	New	Smless	H-40	24"	150 sks	Around shoe
13 3/8"	1051'	0	54.5	New	Smless	J-55	17 1/2"	900 sks	Around shoe

PERFORATIONS

Size of casing	From	To	Size of perforations	Number of rows	Distance between centers	Method of perforations
	ft.	ft.				
	ft.	ft.				
	ft.	ft.				
	ft.	ft.				
	ft.	ft.				

Electrical Log Depths 1051-5551' (Attach Copy of Log)

*act*

WELL SUMMARY REPORT  
(Submit in duplicate)

Operator The Texas Co. Field Clatskanie Area  
Well No. Clatskanie 1 NE1/4 Sec. 30, T. 7N, R. 4W, S. WM W. B. & M.  
Location 517'N & 1274'W of E1/4 corner Elevation above sea level 271' feet  
All depth measurements taken from top of Kelly Bushing, which is 15.3 feet above ground

In compliance with the rules and regulations pursuant to ORS 520 (Chapter 667 OL 1953) the information given herewith is a complete and correct record of the present condition of the well and all work done thereon, so far as can be determined from all available records.

Date June 19, 1946 Signed W.A. Clark  
T.W. Bell J.H. Pills Title Div. Engr.  
Engineer or Geologist Superintendent (President, Secretary or Agent)

Commenced drilling July 2, 1945 Completed drilling Sept. 28, 1945 Drilling tools Cable Rotary  
Total depth 5650' Plugged depth 0 GEOLOGICAL MARKERS DEPTH  
Junk 973' 4 1/2" db and drill collars Keasey 0-730'  
4667-5640' U Eoc Marine Seds  
and Volcs 730-5650'

Commenced producing \_\_\_\_\_ Date \_\_\_\_\_ Flowing/gas lift/pumping (cross out unnecessary words)

Clean oil bbl. per day	Gravity Clean oil	Percent water including emulsion	Gas Mcf. per day	Tubing Pressure	Casing Pressure
Initial production					
Production after 30 days					

CASING RECORD (Present Hole)

Size of casing (A.P.D.)	Depth of shoe	Top of casing	Weight of casing	New or second hand	Seamless or Lapweld	Grade of casing	Size of hole drilled	No. of sacks of cement	Depth of cementing if through perforations
20"	115'	0	78#	New	Smless	H-40	24"	150 sks	Around shoe
13 3/8"	1051'	0	54.5	New	Smless	J-55	17 1/2"	900 sks	Around shoe

PERFORATIONS

Size of casing	From	To	Size of perforations	Number of rows	Distance between centers	Method of perforations
	ft.	ft.				
	ft.	ft.				
	ft.	ft.				
	ft.	ft.				
	ft.	ft.				