

WELL SUMMARY REPORT
(Submit in duplicate)

Operator American Quasar Petroleum Co. Field Wildcat
Well No. Benson Timber 8-14 Sec. 8, T. 6N, R. 4W, Columbia County W. B. & M.
Location 300' FSL 1046' FWL (SW $\frac{1}{4}$) Elevation above sea level 1006.9 feet
All depth measurements taken from top of Kelly Bushing, which is 10.4 feet above ground

In compliance with the rules and regulations pursuant to ORS 520 (Chapter 667 OL 1953) the information given herewith is a complete and correct record of the present condition of the well and all work done thereon, so far as can be determined from all available records.

Date December 7, 1981 Signed [Signature]
Engineer or Geologist _____ Superintendent _____ Title Division Drilling Engineer
(President, Secretary or Agent)

Commenced drilling 11/20/81 @9:00 PM Completed drilling 11/27/81 Drilling tools Cable Rotary
Total depth 2196 Plugged depth Surface GEOLOGICAL MARKERS DEPTH
Junk _____ Kersey Surface
_____ Cowlitz 680
_____ 2nd C&W sand 1420' TVD

Commenced producing Dry hole Date _____ Flowing/gas lift/pumping (cross out unnecessary words)

Initial production
Production after 30 days

Clean oil bbl. per day	Gravity Clean oil	Percent water including emulsion	Gas Mcf. per day	Tubing Pressure	Casing Pressure

CASING RECORD (Present Hole)

Size of casing (A.P.L.)	Depth of shoe	Top of casing	Weight of casing	New or second hand	Seamless or Lapweld	Grade of casing	Size of hole drilled	No. of sacks of cement	Depth of cementing if through perforations
12 $\frac{1}{4}$ "	20'	Surface	-	Conductor					
7"	479'	Surface	20#	New	Seamless	K55	9 7/8"	200	Cemtd to sfc.

PERFORATIONS

Size of casing	From	To	Size of perforations	Number of rows	Distance between centers	Method of perforations
	ft.	ft.				
	ft.	ft.				
	ft.	ft.				
	ft.	ft.				
	ft.	ft.				