

STATE OF OREGON
DEPARTMENT OF GEOLOGY AND MINERAL INDUSTRIES
1069 State Office Building Portland 1, Oregon

HISTORY OF OIL OR GAS WELL

(Submit in duplicate)

In compliance with rules and regulations adopted pursuant to ORS 520.095 (Chapter 667 OL 1953)

Operator Union Oil Co.

Field

Well No. Written - 2

, Sec. 10

, T. 3 S.

R. 3 E.

W. B. & M.

Signed

Title

J. P. Thornhill
Secretary

(President, Secretary or Agent)

Date 10/30/57

It is of the greatest importance to have a complete history of the well. Use this form in reporting the history of all important operations at the well, together with the dates thereof, prior to the first production. Include in your report such information as size of hole drilled to cementing or landing depth of casings, number of sacks of cement used in the plugging, number of sacks or number of feet of cement drilled out of casing, depth at which cement plugs started, and depth at which hard cement encountered. If the well was dynamited, give date, size, position and number of shots. If plugs or bridges were put in to test for water, state kind of material used, position and results of pumping or bailing.

Date

7/25/57

Trudded in with cable tools, 12" hole

Set 45' of 8" casing, tensacks cement

Small gas pocket at 472'

made rainbow at 488', very little

made small rainbow at 508 to 504'

3/8/57

ceased drilling at 500 feet

3/8/57

obtained permission to suspend for 90 days

8/10/57

obtained extension of suspended status for 90 days

10/17/57

Notified Dept. of intention to resume operations

10/21/57

Set up rotary rig, encountered cave in at 274 feet, circulated with heavy mud

10/22/57

circulated all morning, made no headway with cave in

10/25/57

Contacted Dept. by phone, described conditions and gave résumé of log and was given permission to plug according to outlined plan subject to submission of written reports.

10/26/57

Plugged well as follows:

15 foot cement plug on top of cave-in at 274 ft.

20 foot " " from 3' below surface.

Mud fluid between cement plugs separated by wooden plug.

45' of 8" casing cut off 3' below the surface left in the ground with additional cement around the outside at the top.

Plate on top of casing.

13 sacks of cement used.