

HISTORY OF OIL OR GAS WELL

(Submit in duplicate)

In compliance with rules and regulations adopted pursuant to ORS 520.095 (Chapter 667 OL 1953)

Operator Reichhold Energy Corporation

Field Mist

Well No. C.C. #4 R.D. #1 NE/4

, Sec. 15

, T. 6N

R. 5W

W.B. & M.

Signed

Tim Williamson

Title Drilling Superintendent

(President, Secretary or Agent)

Date 7-27-82

It is of the greatest importance to have a complete history of the well. Use this form in reporting the history of all important operations at the well, together with the dates thereof, prior to the first production. Include in your report such information as size of hole drilled to cementing or landing depth of casings, number of sacks of cement used in the plugging, number of sacks or number of feet of cement drilled out of casing, depth at which cement plugs started, and depth at which hard cement encountered. If the well was dynamited, give date, size, position and number of shots. If plugs or bridges were put in to test for water, state kind of material used, position and results of pumping or bailing.

Date	Description
7-10-82	Kill well, nipple up B.O.P.'s, Rigged up Halliburton and pumped 23 sxs. class G cement with 3% cacl to well. Cement was pumped from 2370' - 1780'
7-11-82	Tag cement @ 1781', nipple down B.O.P.'s & weld on 4½" lifting nipple
7-12-82	Rig up McCulloch and run Freepoint-shot casing off @ 729' & laying down same, Rig up Halliburton
7-13-82	Pumped cement from 724' - 229' W.O.C., 83 sxs. class G 3% cacl,
7-14-82	Test B.O.P.'s, polish off cement to 475' drilling to 630'
7-15-82	Drilling to 933'
7-16-82	" " 1479'
7-17-82	" " 1865'
7-18-82	" " 2345'
7-19-82	" " 2812'
7-20-82	" " 2894, T.D. logging W/Schlumberger
7-21-82	Run 4½ casing to 2679.05 & pumped 75 sxs class G cement to well
7-22-82	Pick up 2 3/8 tubing, set @ 2276' & nipple up tree
7-23-82	Run bond log
7-24-82	Perforate & blow well, Released rig 7-24-82

note

2250 McF