

MISCELLANEOUS APPLICATION
 (In compliance with rules and regulations pursuant to ORS 520)

Enerfin Resources Northwest	"Columbia County"	34-31-65R (Bigfoot)
<small>(Company or Operator)</small>	<small>(Lease)</small>	<small>(Well No.)</small>
Sec. <u>31</u> T <u>6N</u> R <u>5W</u>	Surveyed Coordinates:	
SHL= <u>662' North and 2,047' West from the Southeast corner of Section 31</u>		
BHL= <u>971' North and 1,742' West from the Southeast corner of Section 31</u>		
Wildcat: <u>NA</u>	(or) Field Name: <u>Mist Gas</u>	County: <u>Columbia</u>
Date: <u>July 22, 1999</u>	Signature: <u>Rob Lucas</u>	

Use this form for telephone applications to deepen, rework, abandon, or any other proposed procedure on an existing well.

This form becomes a permit when signed and dated by DOGAMI in the box below.

The present condition of the well, including complete casing record, is as follows:

Casing(s):	8-5/8" 24# J-55 ST&C cemented at 502'	$ \begin{array}{r} 25 \text{ SK cement} \\ 321 \text{ ft plug} \\ 62' \\ 21 \\ \hline 1239. \end{array} $
	4-1/2" 10.5# J-55 ST&C cemented at 1,705'	
Perforations:	? SPF from 1,526'-1,542'	Calc. top @ 1239.
Tubing Detail:	? Joints of 2-3/8" 4.7# J-55 EUE hung at ~1,500'	

Following is a detailed account of proposed work:


1. Set cement plug from 1,542'-1,476'.
2. Change hole over to drilling mud.
3. Cut off wellhead and casings. Set cement plug from 25'-surface in 4-1/2" casing and 4-1/2" X 8-5/8" annulus as needed.
4. Restore location as per landowner wishes.

Tag w/ Simpson Bar.

DOGAMI approved July 22, 1999

DOGAMI will tag the cement plug @ or above 1,476'.

by Don E. Dennis



1316' - Top of cement

1305
380
1315' - Top of Tubing

6 joints of tubing dropped in hole when pulling out. Top @ 1315'.