

STATE OF OREGON
DEPARTMENT OF GEOLOGY AND MINERAL INDUSTRIES
1069 State Office Building Portland 1, Oregon

HISTORY OF OIL OR GAS WELL
(Submit in duplicate)

In compliance with rules and regulations adopted pursuant to ORS 520.095 (Chapter 667 OL 1953)

Operator REICHHOLD ENERGY CORPORATION Field MIST
Well No. COLUMBIA COUNTY 41-2 , Sec. 2 , T. 6N R. 5W W. B. & M.

Signed *Tim Williamson*
Title Drilling Superintendent
(President, Secretary or Agent)

Date March 10, 1982

It is of the greatest importance to have a complete history of the well. Use this form in reporting the history of all important operations at the well, together with the dates thereof, prior to the first production. Include in your report such information as size of hole drilled to cementing or landing depth of casings, number of sacks of cement used in the plugging, number of sacks or number of feet of cement drilled out of casing, depth at which cement plugs started, and depth at which hard cement encountered. If the well was dynamited, give date, size, position and number of shots. If plugs or bridges were put in to test for water, state kind of material used, position and results of pumping or bailing.

Date	Description
1-28-82	Spudded well, drilling 9 7/8" surface hole to 369'. Lost circulation - pumped plug. Lost circulation again - pumped 2nd plug.
1-29-82	Pumped lost circulation material.
1-30-82	Pumped more lost circulation material and drilled to 541'
1-31-82	Pumped lost circulation material and established circulation Rigged up Morelli's casing service and ran 12 joints 7" K-55 pipe to a total depth of 518'. Cemented pipe with 200 sacks class H cement with 3% ca. cl. Waiting on cement.
2- 1-82	Pumping top out - waiting on cement nipping up B.O.P.'s
2- 2-82	Testing B.O.P.'s with ODOGAMI and drilling 6 1/4" hole to 1200'
2- 3-82	Drilled to 1750'
2- 4-82	Drilled to 2100'
2- 5-82	Drilled to 2375'
2- 6-82	Drilled to 2865"
2- 7-82	Drilled to total depth of 2875' - logged with Welex
2- 8-82	Plugged well to redrill.