

HISTORY OF OIL OR GAS WELL

(In compliance with rules and regulations pursuant to ORS 520)

Reichhold Energy Corporation Crown Zellerbach 12-1
(Company or operator) (Lease) (Well No.)

Sec. 1 , T. 5N , R. 5W W.B.&M. Surveyed Coordinates: 1902'S & 1001' E
of NW corner, Section 1

Wildcat: Yes (or) Field Name: 791.19 County: Columbia

Signature: *Gold Thomas*
Date: July 8, 1985 Position: Field Operations Supervisor

Use this form in reporting the daily operations at the well. (Operator may use his own forms, but heading of this form must also be completed and submitted.) Please submit a complete history of the well. Include such information as bit sizes, mud weights, casing sizes and depths set, amount of cement used, drilling depths, fishing, logging, perforating, and plugging procedures, and anything else pertinent to the operation. Do not include lithology.

Date

6/21/85 Weld conductor, mix mud & drlg 12 $\frac{1}{2}$ " hole to 271
6/22/85 Drlg to 412' Run 9 jts 8 5/8" casing to 403 & cement with 225 sx class "G" cement. WOC. Cut off casing & weld on wellhead and test. Nipple up BOP's
6/23/85 WOC. Pressure test BOP with Bill King witnessing. Drlg float, cement & shoe. Drlg. 7 7/8" hole to 723.
6/24/85 Drlg & wiper trip. Drlg to 1534'
6/25/85 Drlg to 1721' or TD. Wiper trip to shoe. Run wireline logs. RIH and circ. & condition hole
6/26/85 Circ. Lay down drill collars. RIH open-ended to 1320' & set plug with 47 sx. Pull up 2 stands & circ. POH & lay down drillpipe. Rig up to run casing & run. Won't go to bottom. Circ. & condition mud. Run 29 jts to 1103'.
6/27/85 Circ. hole clean. Rig up Halliburton & cement with 250 sx class "G" 3% KCl, 1% CaCl, 1% CFR3, .1% Halad 4. Set casing slips. WOC.
6/28/85 WOC. Nipple up tubing head & test to 3000 psi.
6/29/85 WOC. RIH with tubing and change over to 4% KCl. POH with tubing and stand back.
6/30/85 Rig up WELEX and run bond log. RIH with tubing & land @ 952. Nipple up tree. RIH & perforate 989' - 1000' & 1004' - 1006'. Displace KCl with nitrogen & test. Tested @ 1.1 MMCF/D thru 23/64" choke SICP = 430 SITP = 434.

RELEASED RIG @ 12 MIDNIGHT 6/30/85

DEPT. OF GEOLOGY
A MINERAL INDUSTRY

JUL 10 1985

RECEIVED - PILD