

WELL SUMMARY REPORT  
(Submit in duplicate)

Operator Diamond Shamrock Corporation Field Wildcat  
 Well No. Clatsop County 33-11 Sec. 11, T. 6N, R. 6W, W. B. & M.  
 Location 1858' N & 1845' W of SE Corner Elevation above sea level 928 feet  
 All depth measurements taken from top of KB, which is 12 feet above ground

In compliance with the rules and regulations pursuant to ORS 520 (Chapter 667 OL 1953) the information given herewith is a complete and correct record of the present condition of the well and all work done thereon, so far as can be determined from all available records.

Date October 26, 1983

Signed

John C. SeelingAlan SeelingWes ChildersTitle Sr. Drilling EngineerGeologistSuperintendent(President, Secretary or Agent)Commenced drilling 5-22-83 Completed drilling 6-3-83 Drilling tools Rotary

Total depth	Plugged depth	GEOLOGICAL MARKERS		DEPTH
<u>4223'</u>	<u>Surface</u>	<u>Cowlitz</u>		<u>3610</u>
<u>Junk N/A</u>		<u>C&amp;W Sands</u>		<u>3960</u>

Commenced producing N/A Date                      Flowing/gas lift/pumping  
(cross out unnecessary words)

Initial production  
Production after 30 days

Clean oil bbl. per day	Gravity Clean oil	Percent water including emulsion	Gas Mcf. per day	Tubing Pressure	Casing Pressure
<u>N/A</u>					
<u>N/A</u>					

## CASING RECORD (Present Hole)

Size of casing (A.P.L.)	Depth of shoe	Top of casing	Weight of casing	New or sec- ond hand	Seamless or Lapweld	Grade of casing	Size of hole drilled	No. of sacks of cement	Depth of cement- ing if through perforations
<u>9 5/8"</u>	<u>1004'</u>	<u>Surface</u>	<u>36.0#</u>	<u>New</u>	<u>SMLSS</u>	<u>K-55</u>	<u>13 1/2"</u>	<u>750</u>	<u>N/A</u>

## PERFORATIONS

Size of casing	From	To	Size of perforations	Number of rows	Distance between centers	Method of perforations
<u>N/A</u>	<u>ft.</u>	<u>ft.</u>				
	<u>ft.</u>	<u>ft.</u>				
	<u>ft.</u>	<u>ft.</u>				
	<u>ft.</u>	<u>ft.</u>				
	<u>ft.</u>	<u>ft.</u>				