

PLUGGING RECORD

The owner or operator of any oil or gas well or stratigraphic hole shall file this form with the Director of the State of Oregon Department of Geology and Mineral Industries setting forth in detail the method used in plugging such well. The form must be filed within twenty (20) days after plugging for oil and gas wells, or within sixty (60) days for stratigraphic holes.

Rule L of rules and regulations adopted pursuant to ORS 520.095 (1) (13) (Chapter 667 OL 1953)

Operator American Quasar Petroleum Co. Field Wildcat
Pool _____
County Columbia

ADDRESS ALL CORRESPONDENCE CONCERNING THIS FORM TO:

204 Superior Bldg.
Street 201 North Wolcott St. City Casper State Wyoming 82601
Lease Name Crown Zellerbach Well No. 14-21 Sec. 14 T. 5N R. 5W
Date well was plugged February 23 1980.

Was the well filled with mud laden fluid, according to regulations of the Board of the State of Oregon Department of Geology and Mineral Industries? Yes

How was the mud applied? Left in place Were plugs used? Yes If so, show all shoulders left for casing, depth of each, and size of casing, size and kind of plugs used, and depths placed. Also amount of cement and rock.

Use additional sheets if necessary. Set 20' of 12.5" csg. - cmt. to surf. w/4 yds ready-mix.
Set 515' of 7" csg. - cmt. to surf. w/250 sx Class "G".

50-sk Class "G" plug - 1146-875' - 9.6# mud.
550-sk Class "G" plug - 595- 326'; tagged plug after 6 hrs. - OK @ 355'.
9.6# mud to surface - 10 sx Class "G" on surface.

Was notice given, before plugging, to all available adjoining lease and land owners? No

American Quasar Petroleum Co.
By: John F. Sindelar
(Operator)
John F. Sindelar

AFFIDAVIT

State of Wyoming
County of Natrona

I, W. L. Highsmith, being duly sworn, say that I have knowledge of the facts stated herein, that they are true and correct, and that I am authorized to make this report.

Subscribed and sworn to before me this 25th day of February 1980

Notary public ~~for and for~~ W. L. Highsmith
W. L. Highsmith