

RECEIVED - PTLD

MAY 17 1985

DEPT. OF GEOLOGY
& MINERAL INDUSTRIES

HISTORY OF OIL OR GAS WELL

(In compliance with rules and regulations pursuant to ORS 520)

Reichhold Energy Corporation Crown Zellerbach 34-26
(Company or operator) (Lease) (Well No.)

Sec. 26 , T. 5N , R. 4W W.B.&M. Surveyed Coordinates: 1255' S & 632'
E of center of section

Wildcat: Yes (or) Field Name: _____ County: Columbia

Date: May 15, 1985 Signature: Bob Thomas
Position: Field Operations Supervisor

Use this form in reporting the daily operations at the well. (Operator may use his own forms, but heading of this form must also be completed and submitted.) Please submit a complete history of the well. Include such information as bit sizes, mud weights, casing sizes and depths set, amount of cement used, drilling depths, fishing, logging, perforating, and plugging procedures, and anything else pertinent to the operation. Do not include lithology.

Date	
4/21/85	Mix mud & spud. Drlg 12 1/4" hole to 352'
4/22/85	Drlg. to 654', Wiper trip.
4/23/85	Run 14 jts 9 5/8" 36# casing to 633'. Cement with 260 sx Class "G" cement. Cut off casing. Weld on casing head and test.
4/24/85	Nipple up BOE & test with Bill King witnessing. Drlg. 8 3/4" hole to 925.
4/25/85	Drlg. to 1584'. Wiper trip, ream 150' to bottom.
4/26/85	Drlg. to 2103'. Wiper trip.
4/27/85	Drlg. to 2763'.
4/28/85	Trip for new bit #2. Drlg. to 3250'.
4/29/85	Drlg. to 3748'. Wiper trip.
4/30/85	Drlg. to 3821'. Trip for new bit #3. Drlg to 4183'.
5/1/85	Drlg. to 4785'. Wiper trip.
5/2/85	Drlg. to 4840'. Trip for new bit #4. Drlg. to 5033'.
5/3/85	Drlg. to 5294'. Wiper trip.
5/4/85	Drlg. to 5709'.
5/5/85	Drlg. to 5839' or total depth. Wiper trip. POH for loggers. Rig up Schlumberger and run wire line logs.
5/6/85	Wire line logs. Lay down DC's & D.P. RIH open-ended to 4318' & WOC.
5/7/85	WOC & circ. Set plug @ 4318' - 4118' with 73 sx. POH. Laying down DP to 700'. Set plug with 110 sx. WOC. Tag plug @ 498' with Bill King witnessing.

RELEASED RIG @ 3:00 PM - MAY 8, 1985