

STATE OF OREGON
DEPARTMENT OF GEOLOGY AND MINERAL INDUSTRIES
1069 State Office Building Portland 1, Oregon

RECEIVED

MAY 17 1984

DEPT OF GEOLOGY
& MINERAL INDUSTRIES

HISTORY OF OIL OR GAS WELL
(Submit in duplicate)

In compliance with rules and regulations adopted pursuant to ORS 520.095 (Chapter 667 OL 1953)

Operator Reichhold Energy Corp.

Field Deer Creek

Well No. Crown Zellerbach 34-28 , Sec. 28

, T. 6N

R. 4W

W.B. G.M.

Signed

Title Field Operations Supervisor
(President, Secretary or Agent)

Date May 15, 1984

It is of the greatest importance to have a complete history of the well. Use this form in reporting the history of all important operations at the well, together with the dates thereof, prior to the first production. Include in your report such information as size of hole drilled to cementing or landing depth of casings, number of sacks of cement used in the plugging, number of sacks or number of feet of cement drilled out of casing, depth at which cement plugs started, and depth at which hard cement encountered. If the well was dynamited, give date, size, position and number of shots. If plugs or bridges were put in to test for water, state kind of material used, position and results of pumping or bailing.

- Date /30/84 Spudded well and drilling 12 1/4" hole to 481'.
- /01/84 Wiper trip and circ. Ran 11 jts of 8 5/8" casing to 470.28 and cement with 250 sx Class G 2% CaCl cement. Wait on cement.
- 5/2/84 Nipple up BOP and pressure test with Bill King witnessing. Drilling float and cement. Drilling 7 7/8" hole to 705.
- 5/3/84 Drilling to 1412.
- 5/4/84 Drilling to 2086.
- 5/5/84 Drilling to 2538.
- 5/6/84 Drilling to 3018.
- 5/7/84 Drilling to 3403.
- 5/8/84 Drilling to 3654 or TD. Wiper trip to shoe, RIH with logging tools. Stuck tool @ 2300'±. Pull out of rope socket.
- 5/9/84 RIH with fishing tools and retrieve fish. RIH and circ. Wiper trip to shoe.
- 5/10/84 RIH with logging tools. RIH with drill pipe to 3457 and set plug to 3107 with 103 sx of Class G 1% CaCl cement. Pull up to 531' and pump plug to 380' with 78sx Class G 1% cement. WOC & rig down.
- 5/11/84 Tagged top plug @ 460 with Dennis Olmstead witnessing. Plug fell so pumped 17 sx cement to 410'.

Release rig @ 4 p.m.



