

STATE OF OREGON  
DEPARTMENT OF GEOLOGY AND MINERAL INDUSTRIES  
1069 State Office Building, Portland 1, Oregon

WELL SUMMARY REPORT  
(Submit in duplicate)

Operator Reserve Oil and Gas Company Field Golden Valley Area

Well No. "Esmond" No. 1 Sec. 7, T. 12S, R. 1W, \_\_\_\_\_ W. B. & M.

Location 1194'N, 575'W of S/4 Corner Elevation above sea level 475+ feet

All depth measurements taken from top of Kelly Bushing, which is 12 feet above ground

In compliance with the rules and regulations pursuant to ORS 520 (Chapter 667 OL 1953) the information given herewith is a complete and correct record of the present condition of the well and all work done thereon, so far as can be determined from all available records.

Date September 12, 1962 Signed *R.P. Mangold*

W. L. D'Olier T. Gray  
Engineer or Geologist Superintendent Title Manager-Field Operations  
(President, Secretary or Agent)

Commenced drilling 5-25-62 842' completed drilling 9-6-62 Drilling tools Cable Rotary

Total depth 8603' Plugged depth 6925' GEOLOGICAL MARKERS DEPTH

Junk \_\_\_\_\_

Suspended 9-9-62

Commenced producing Never Date \_\_\_\_\_ Flowing/gas lift/pumping (cross out unnecessary words)

	Clean oil bbl. per day	Gravity Clean oil	Percent water including emulsion	Gas Mcf. per day	Tubing Pressure	Casing Pressure
Initial production						
Production after 30 days						

CASING RECORD (Present Hole)

Size of casing (A.P.L.)	Depth or shoe	Top of casing	Weight of casing	New or sec- ond hand	Seamless or Lapweld	Grade of casing	Size of hole drilled	No. of sacks of cement	Depth of cement- ing if through perforations
10-3/4"	891'	surf.	32.75	New	SMLS.	H-40	15-1/2	347	

PERFORATIONS

Size of casing	From	To	Size of perforations	Number of rows	Distance between centers	Method of perforations
	ft.	ft.				
	ft.	ft.				
	ft.	ft.				
	ft.	ft.				
	ft.	ft.				

Electrical Log Depths 2943', 7109', 8541', 8604' (Attach Copy of Log)