

WELL SUMMARY REPORT
 (Submit in duplicate)

Operator American Quasar Petroleum Co. Field Lebanon Area
 Well No. 9-12 Sec. 9, T 12S, R 2W, W. B. & M.
 Location 990' FWL, 1980' FNL Elevation above sea level 329 feet
 All depth measurements taken from top of KB, which is 340 feet above ground

In compliance with the rules and regulations pursuant to ORS 520 (Chapter 667 OL 1953) the information given herewith is a complete and correct record of the present condition of the well and all work done thereon, so far as can be determined from all available records.

Date 5/26/81 Signed J.T. Braun FOR WR SEIDEL
Tim Smith Kelton Mann Division Operations Manager
 Engineer or Geologist Superintendent (President, Secretary or Agent)

Commenced drilling 1/18/81 Completed drilling 2/14/81 Drilling tools Cable Rotary
 Total depth 4692 Plugged depth 4630 GEOLOGICAL MARKERS DEPTH
 Junk _____ Base Surface Volcanics 2250
 _____ Top Eugene 2520
 _____ Top Eugene Prod. Sands 2990
 _____ Top Fisher Volcanics 3830

Commenced producing 5/18/81 Date 5/18/81 Flowing/~~gas lift/complex~~
 (cross out unnecessary words)

Initial production
 Production after 30 days

Clean oil bbl. per day	Gravity Clean oil	Percent water including emulsion	Gas Mcf. per day	Tubing Pressure	Casing Pressure
		0	200	400	--

CASING RECORD (Present Hole)

Size of casing (A.P.L.)	Depth of shoe	Top of casing	Weight of casing	New or second hand	Seamless or Lapweld	Grade of casing	Size of hole drilled	No. of sacks of cement	Depth of cementing if through perforations
14" conductor @ 130' 7 Yards Ready Mix									
9 5/8"	521	surface	36#	new	seamless	K55	12 1/4"	300	
7"	2116	surface	20#	new	seamless	K55	8 3/4"	440	
4 1/2"	4671	surface	10.5#	new	seamless	K55	6 1/2"	460	

PERFORATIONS

Size of casing	From	To	Size of perforations	Number of rows	Distance between centers	Method of perforations
4 1/2"	3095 ft.	3100 ft.	9/16"	4 SPF		Sqzd w/100 sx
4 1/2"	3004 ft.	3027 ft.	9/16"	4 SPF		
	ft.	ft.				
	ft.	ft.				
	ft.	ft.				