

STATE OF OREGON  
DEPARTMENT OF GEOLOGY AND MINERAL INDUSTRIES  
1069 State Office Building, Portland 1, Oregon

WELL SUMMARY REPORT  
(Submit in duplicate)

Operator Oregon Coastal Corp Field Bandon Area  
Well No. John Coy 1 SE1/4 Sec. 4, T. 29S, R. 11W, WM W. B. & M.  
Location \_\_\_\_\_ Elevation above sea level 200' feet

All depth measurements taken from top of \_\_\_\_\_, which is \_\_\_\_\_ feet above ground

In compliance with the rules and regulations pursuant to ORS 520 (Chapter 667 OL 1953) the information given herewith is a complete and correct record of the present condition of the well and all work done thereon, so far as can be determined from all available records.

Date 1953 Signed E.W. McDowell  
\_\_\_\_\_  
Engineer or Geologist Superintendent Title President  
(President, Secretary or Agent)

Commenced drilling 1953 Completed drilling 1953 Drilling tool Cable Rotary  
Total depth 1894 Plugged depth \_\_\_\_\_ GEOLOGICAL MARKERS DEPTH  
Junk \_\_\_\_\_ Spud in Terrace  
Bottom in L Coaledc

Commenced producing \_\_\_\_\_ Date \_\_\_\_\_ Flowing/gas lift/pumping  
(cross out unnecessary words)

	Clean oil bbl. per day	Gravity Clean oil	Percent water including emulsion	Gas Mcf. per day	Tubing Pressure	Casing Pressure
Initial production						
Production after 30 days						

CASING RECORD (Present Hole)

Size of casing (A.P.L.)	Depth of shoe	Top of casing	Weight of casing	New or sec- ond hand	Seamless or Lapweld	Grade of casing	Size of hole drilled	No. of sacks of cement	Depth of cement- ing if through perforations
<u>10"</u>	<u>205'</u>	<u>0</u>						<u>?</u>	

PERFORATIONS

Size of casing	From	To	Size of perforations	Number of rows	Distance between centers	Method of perforations
	ft.	ft.				
	ft.	ft.				
	ft.	ft.				
	ft.	ft.				
	ft.	ft.				

Electrical Log Depths \_\_\_\_\_ (Attach Copy of Log)