

MISCELLANEOUS NOTICES AND REPORTS ON WELLS AND STRATIGRAPHIC HOLES
 (Submit in triplicate)

This is a combined form, use only portions pertinent to your needs.

To comply with rules and regulations adopted pursuant to ORS 520 (Chapter 667 OL 1953).

Notices		Reports	
Indicate nature of notice by checking below:		Indicate nature of report by checking below:	
Notice of intention to plug well		Report on plugging well (use form 5)	
Notice of intention to make formation test		Report on making formation test	
Notice of intention to make production test		Report on making production test	
Notice of intention to abandon well	X	Report on abandoning well	
Notice of intention to test casing shut-off		Report on testing casing shut-off	
Notice of intention to redrill or deepen well		Report on redrilling or deepening well	
Notice of intention to shoot or chemically treat well		Report on shooting or chemically treating well	
Notice of intention to complete well		Report on completion of well	

Submit notices in triplicate before the work specified is to begin. A copy will be returned to the sender on which will be given the approval, with any modifications considered advisable, or the rejection by the Department or agent, of the plan submitted.

Submit reports in triplicate within 20 days after the work specified is completed.

Portland, Oregon, July 18 19 57

Department of Geology and Mineral Industries
 Portland, Oregon

Following is a report on the work done and the results obtained at the Sunray Mid-Continent -
 notice of intention to do certain work as described below Company or Operator
Lloyd Corporation Well No. Kappler #1 in
 Lease

of sec. 12, T. 2 N., R. 2 W., W.B. & M., field,
Multnomah County. The dates of this work ~~was~~ will be July 18, 1957.

Notice of intention to do the work was ~~(insert)~~ submitted ~~by letter~~ by letter July 18 19 57
 and approval of the proposed plan was ~~(insert)~~ obtained. (Cross out incorrect words.)

The present condition of the well, including complete casing record, is as follows (Use additional sheets as needed):

- 10-3/4" casing cemented from surface to 608 feet.
- 9" hole from 608 feet to 1666 T.D.

FOLLOWING IS A COMPLETE DETAILED ACCOUNT OF WORK DONE AND RESULTS OBTAINED
 (USE ADDITIONAL SHEETS AS NEEDED) PROPOSED WORK

1. Lay a 100-sack cement plug between 548 and 708 feet.
2. Lay a 10-foot cement plug at the surface.
3. Place a steel plate at the surface.
4. Weld an iron bar (4'± long) in upright position on steel plate.

Last produced Dry hole (date) (net oil) (gravity) (cut)

Approved July 18 19 57
 except as follows
No exceptions.

DEPARTMENT OF GEOLOGY AND MINERAL INDUSTRIES
 By [Signature]
 Director

Sunray Mid-Continent Oil Company
 Company or operator
 By Richard A. Eckhart
 Position Geologist

Send communications regarding well to
 Name Sunray Mid-Continent Oil Company
 Address 714 W. Olympic Boulevard
Los Angeles 15, California