

RESTRICTION
CONFIDENTIAL
LIFTEDHISTORY OF OIL OR GAS WELL
(Submit in duplicate)

In compliance with rules and regulations adopted pursuant to ORS 520.095 (Chapter 667 OL 1953)

Operator **Standard Oil Company of California** Field **Wildcat**
Well No. **Kirkpatrick #1**, Sec. **6**, T. **4S** R. **21E** W.B. & M.

Date

Signed *J. Hastings*
Title **Division Exploration Supervisor**
(President, Secretary or Agent)

It is of the greatest importance to have a complete history of the well. Use this form in reporting the history of all important operations at the well, together with the dates thereof, prior to the first production. Include in your report such information as size of hole drilled to cementing or landing depth of casings, number of sacks of cement used in the plugging, number of sacks or number of feet of cement drilled out of casing, depth at which cement plugs started, and depth at which hard cement encountered. If the well was dynamited, give date, size, position and number of shots. If plugs or bridges were put in to test for water, state kind of material used, position and results of pumping or bailing.

Date

Set 22' of 18½" conductor pipe
Spudded January 31, 1957
Drilled 9-7/8" hole to 872'
Reamed to 17½" hole to 205'
Cemented 13-3/8" surface casing at 205' with 185 sacks
Drilled 9-7/8" hole to 8726'

No water zones or hydrocarbon shows of interest were encountered, although the well was left open and filled with fresh water above 1655' and turned over to the landowner who will attempt to produce fresh water from this upper zone. A momentary loss of circulation occurred while drilling at 1955' and very slight partial mud losses occurred on several occasions while drilling between 3300' & 3600'.

A cement plug of 150 sacks of construction-type cement was pumped into place through 4½" open end drill pipe hung at 1943'. Approximately 10 hours later the top of solid cement was located at 1655'. Although the well was then returned to the landowner as a water well, a steel plate was welded across the casing, at the surface, for complete safety. Well abandoned June 22, 1957.