

WELL SUMMARY REPORT
 (Submit in duplicate)

Operator Nahama & Weagant Energy Co. Field -----
 Well No. KLOHS #1 Sec. 6, T 3S, R 2W, ----- W. B. & M.
 Location 180'S & 1115'W fr NE Corner Elevation above sea level 910 (GL) feet
 All depth measurements taken from top of Sec 6 Kelly Bushing, which is 13.5 feet above ground

In compliance with the rules and regulations pursuant to ORS 520 (Chapter 667 OL 1953) the information given herewith is a complete and correct record of the present condition of the well and all work done thereon, so far as can be determined from all available records.

Date October 20, 1982 Signed Leland Cecil
Leland B. Cecil Title Leland B. Cecil, Agent
 Engineer or Geologist Superintendent (President, Secretary or Agent)

Commenced drilling Sept. 15, 1982 Completed drilling Oct. 12, 1982 Drilling tools Rotary
 Total depth 5870' Plugged depth P & A GEOLOGICAL MARKERS DEPTH
 Junk NONE

Commenced producing N.A. Date _____ Flowing/gas lift/pumping (cross out unnecessary words)

	Clean oil bbl. per day	Gravity Clean oil	Percent water including emulsion	Gas Mcf. per day	Tubing Pressure	Casing Pressure
Initial production						
Production after 30 days						

CASING RECORD (Present Hole)

Size of casing (A.P.L.)	Depth of shoe	Top of casing	Weight of casing	New or second hand	Seamless or Lapweld	Grade of casing	Size of hole drilled	No. of sacks of cement	Depth of cementing if through perforations
8 5/8"	623'	Surf*	24#	New	ERW	J-55	14 3/4"	600cf	---
		*	Cut-off 5' below ground level.						

PERFORATIONS

Size of casing	From	To	Size of perforations	Number of rows	Distance between centers	Method of perforations
	ft.	ft.				
	ft.	ft.				
	ft.	ft.				
	ft.	ft.				
	ft.	ft.				

Electrical Log Depths 5870' (Attach Copy of Log)