

STATE OF OREGON
DEPARTMENT OF GEOLOGY AND MINERAL INDUSTRIES

800 NE Oregon St #28 Portland, OR 97201

HISTORY OF OIL OR GAS WELL
(In compliance with rules and regulations pursuant to ORS 520)

Enerfin Resources Northwest

"Longview Fibre"

32-20-65R

(Company or Operator)

(Lease)


(Well No.)

Sec. 20 T 6N R 5W Surveyed Coordinates:

SHL= 1,561' South and 1,334' West of the Northeast corner of Sec. 20

BHL=

Wildcat: NA (or) Field Name: Mist Gas County: Columbia

Signature: 

Date: February 25, 2003

Position: Consultant

Use this form in reporting the daily operations at the well. (Operator may use his own forms, but heading of this form must also be completed and submitted.) Please submit a complete history of the well. Include such information as bit sizes, mud weights, casing sizes and depths set, amount of cement used, drilling depths, fishing, logging, perforating, and plugging procedures, and anything else pertinent to the operations. Do not include lithology.

Date

- February 14, 2003 Moved in and rigged up Taylor Rig #WO1. Removed 3-1/8" 3M X 2" FPT flange. Installed 3-1/8" 3M X 4" MPT flange. Installed and function tested 4" 3M annular BOPE on production tree. Pulled tubing hangar and lowered tubing tail to 2,692'. Equalized 25 sx of Class "G" cement. Pulled out of hole to ~800'. Secured rig and shut well in.
- February 15, 2003 Opened well. Ran in hole and located TOC at 2,120' (witnessed and approved by Robert Houston-DOGAMI). **Cement plug from 2,120'-2,692'**. Changed hole over to 10 PPG drilling mud. Laid down 1-1/4" tubing. Removed BOPE. Removed 7-1/16" 3M X 3-1/8" 3M production tree. Set 10 sx surface cement plug from 25'. **Cement plug from surface-25'**. Rigged down hoist.
- February 16, 2003 Loaded out rig equipment and 1-1/4" tubing.
- February 19, 2003 Cut off wellhead and cut casings 5' below ground level. Backfilled cellar, abandoned pipeline, and restored location to Longview Fibre's specifications.

RECEIVED
MAR - 3 2003
Mined Land Reclamation