

WELL HISTORY

Reichhold Energy Corporation
Well Libel No. 2

Section 15-6N-5W, W.B. & M.
Columbia County, Oregon

September 1979

- 22, Paul Graham Drilling and Service Company moved in Rig No.1 and rigged up.
Spudded in at 9:00 P.M. with 9-7/8" bit and drilled ahead.
55' Clay and Sand
- 23, 397' Clay and Sand
Ran 10 joints of 7" 20# K casing equipped with a guide shoe and cemented around shoe at 397' with 150 sacks of Class II cement. Cement in place at 10:15 A.M. Had approximately 40 Cu.Ft. of cement returns at surface.
Landed casing and installed 6" Series 900 screw on casing head.
Installed and tested BOP equipment.
- 24, Drilled out cement and shoe with 6-1/4" bit and drilled ahead.
1,752' Clay
- 25, 2,857' Clay and Sand.
- 26, Ran Welex Induction-electric Log from 398' to 2,834'.
Ran Welex Compensated Acoustic Velocity Log from 398' to 2,835'
Ran Welex Dipmeter.
Plug No. 1: Hung drill pipe at 2,350' and pumped in and equalized 40 sacks of Class II cement. Calculated to fill to 2,134'.
Cement in place at 11:30 P.M.
Plug No. 2: Hung drill pipe at 1,652' and pumped in and equalized 40 sacks of Class II cement. Calculated to fill to 1,436'.
Cement in place at 12 midnight.
- 27, Plug No. 3: Hung drill pipe at 610' and pumped in and equalized 75 sacks of Class II cement. Cement in place at 12:30 A.M.

-1-

WELL HISTORY

Reichhold Energy Corporation
Well Libel No. 2

Section 15-6N-5W, W.B. & M.
Columbia County, Oregon

September 1979

- 27, Located top of Plug No. 3, at 365'.
Location approved by Department of Geology and Mineral Industries.
Waited on orders
- 28, Laid down drill pipe.
Removed casing head.
Capped 7" casing at surface.
Well suspended in this condition.

-2-