

UNITED STATES DEPARTMENT OF THE INTERIOR GEOLOGICAL SURVEY

SUBMIT IN TRIPPLICATE (Other instructions on reverse side)

Form approved. Budget Bureau No. 42-R1424

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use "APPLICATION FOR PERMIT" for such proposals.)

1. OIL WELL [] GAS WELL [] OTHER Wildcat
2. NAME OF OPERATOR Shell Oil Company
3. ADDRESS OF OPERATOR 1008 West 6th Street, Los Angeles, Calif. 90054
4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements. See also space 17 below.) At surface 5985' FSL & 5051' FWL of P 087 lease
14. PERMIT NO.
15. ELEVATIONS (Show whether DF, RT, CR, etc.) R.T. 67' above MLLW. Water depth 325'
12. COUNTY OR PARISH 13. STATE Oregon

16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data
NOTICE OF INTENTION TO: TEST WATER SHUT-OFF [] PULL OR ALTER CASING [] MULTIPLE COMPLETE [] ABANDON* [X] CHANGE PLANS []
SUBSEQUENT REPORT OF: WATER SHUT-OFF [] REPAIRING WELL [] FRACTURE TREATMENT [] ALTERING CASING [] SHOOTING OR ACIDIZING [] ABANDONMENT* [] (Other) []

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)

With 24" x 13-3/8" casing cemented at 542', 11-3/4" casing cemented at 2807' and 9-5/8" casing cemented at 4179', and T.D. at 8353', plan to plug well as follows:

- 1. Circulated hole with 111#/cf oil base mud from T.D. to surface using rig pumps.
2. Set Halliburton "DMS" bridge plug at 4079'+ and displace all of oil base mud in circulation system below the bridge plug.
3. Using Halliburton pumps place cement plug from 4079'+ to 3879'+. Test plug with 15,000# weight.
4. Using Halliburton pumps place cement plug from 480'+ to 422'+.
5. Shear subconductor and recover all equipment to a depth at least 3' below ocean floor.

NOTED OCT 19 1965 CYPHER

NOTED OCT 19 1965 SCHAMBECK

NOTED - SOLANAS

18. I hereby certify that the foregoing is true and correct
SIGNED [Signature] TITLE Div. Exploitation Engineer DATE 10-18-65
APPROVED BY [Signature] TITLE Los Angeles District Engineer DATE OCT 19 1965

*See Instructions on Reverse Side

UNITED STATES DEPARTMENT OF THE INTERIOR GEOLOGICAL SURVEY

SUBMIT IN TRIPPLICATE (Other instructions on reverse side)

Form approved. Budget Bureau No. 42-R1424

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use "APPLICATION FOR PERMIT" for such proposals.)

1. OIL WELL [] GAS WELL [] OTHER Wildcat
2. NAME OF OPERATOR Shell Oil Company
3. ADDRESS OF OPERATOR 1008 West 6th Street, Los Angeles, California 90054
4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements. See also space 17 below.) At surface 5,985' FSL & 5,051' FWL of P 087 Lease
14. PERMIT NO.
15. ELEVATIONS (Show whether DF, RT, CR, etc.) Water R.T. Approx. 67' above MLLW, depth 320'
12. COUNTY OR PARISH 13. STATE Oregon

16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data
NOTICE OF INTENTION TO: TEST WATER SHUT-OFF [] PULL OR ALTER CASING [] MULTIPLE COMPLETE [] ABANDON* [X] CHANGE PLANS []
SUBSEQUENT REPORT OF: WATER SHUT-OFF [] REPAIRING WELL [] FRACTURE TREATMENT [] ALTERING CASING [] SHOOTING OR ACIDIZING [] ABANDONMENT* [] (Other) []

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)

As a result of severe hole sloughing, we propose the following change in plans:

- 1. Set a cement plug from 4600' to the shoe of the 9-5/8" casing at 4179'. (The maximum depth reached was 5218')
2. Change over to oil-base mud.
3. Drill to 4240', kickoff the cement plug, and redrill to total depth (10,000'+).

Verbal permission to proceed with this proposal was received from Mr. J. H. Fackler on September 16, 1965

NOTED - SOLANAS

NOTED SEP 30 1965 CYPHER

NOTED SEP 30 1965 SCHAMBECK

18. I hereby certify that the foregoing is true and correct
SIGNED [Signature] TITLE Div. Exploitation Engineer DATE September 17, 1965
APPROVED BY [Signature] TITLE Los Angeles District Engineer DATE SEP 1965

*See Instructions on Reverse Side