

1984

WELL SUMMARY REPORT
 (Submit in duplicate)

DEPT. OF GEOLOGY
 OREGON

Operator Reichhold Energy Corporation Field Mist
 Well No. Polak 31-12 Sec. 12, T. 6N, R. 5W, W. B. G. M.
 Location 1161'E & 424' S of N $\frac{1}{4}$ corner Elevation above sea level 1140.32 feet
 All depth measurements taken from top of Kelly Bushing, which is 11.4 feet above ground

In compliance with the rules and regulations pursuant to ORS 520 (Chapter 667 OL 1953) the information given herewith is a complete and correct record of the present condition of the well and all work done thereon, so far as can be determined from all available records.

Date 12/4/84 Signed Bob Thomas
 Title Field Operations Supervisor
 (President, Secretary or Agent)
 Engineer or Geologist _____ Superintendent _____

Commenced drilling 10/31/84 Completed drilling 11/10/84 Drilling tools Cable Rotary

Total depth	Plugged depth	GEOLOGICAL MARKERS	DEPTH
<u>2750</u>	<u>Surface</u>		
Junk _____			

Commenced producing _____ Date _____ Flowing/gas lift/pumping (cross out unnecessary words)

	Clean oil bbl per day	Gravity Clean oil	Percent water including emulsion	Gas Mcf. per day	Tubing Pressure	Casing Pressure
Initial production						
Production after 30 days						

CASING RECORD (Present Hole)

Size of casing (A.P.L.)	Depth of shoe	Top of casing	Weight of casing	New or second hand	Seamless or Lapweld	Grade of casing	Size of hole drilled	No. of sacks of cement	Depth of cementing if through perforations
<u>8 5/8</u>	<u>632</u>	<u>Surface</u>	<u>24#</u>	<u>New</u>	<u>Seamless</u>	<u>K-55</u>	<u>12$\frac{1}{4}$</u>	<u>665</u>	

PERFORATIONS

Size of casing	From	To	Size of perforations	Number of rows	Distance between centers	Method of perforations
	ft.	ft.				
	ft.	ft.				
	ft.	ft.				
	ft.	ft.				
	ft.	ft.				