

STATE OF OREGON
DEPARTMENT OF GEOLOGY AND MINERAL INDUSTRIES
1069 State Office Building Portland 1, Oregon

RECEIVED 071

SEP 10 1984

DEPT OF GEOLOGY

HISTORY OF OIL OR GAS WELL

(Submit in duplicate)

In compliance with rules and regulations adopted pursuant to ORS 520.095 (Chapter 667 OL 1953) Permit #263

Operator CHAMPLIN PETROLEUM COMPANY Field Wildcat

Well No. #1 Puckett 13-36 , Sec. 36 , T. 8N R. 5W W. B. & M.

Date

8-30-84

Signed

Title

(President, Secretary or Agent)

It is of the greatest importance to have a complete history of the well. Use this form in reporting the history of all important operations at the well, together with the dates thereof, prior to the first production. Include in your report such information as size of hole drilled to cementing or landing depth of casings, number of sacks of cement used in the plugging, number of sacks or number of feet of cement drilled out of casing, depth at which cement plugs started, and depth at which hard cement encountered. If the well was dynamited, give date, size, position and number of shots. If plugs or bridges were put in to test for water, state kind of material used, position and results of pumping or bailing.

Date

- 6/24-6/26/84 Spudded 12¼" hole. Drilled to 512'. Ran guide shoe, 1 jt. 9-5/8" 40# J-55 LT&C casing, insert float, 9 jts. 9-5/8" 40# J-55 LT&C, 2 jts. 9-5/8" 36# J-55, ST&C set @ 499'. Cemented w/300 sx Class "G" w/3% CaCl₂. Circulated 30 bbls to surface. Plug down @ 3:30 p.m. 6-26-84.
- 6/27-7/8/84 Drilled 8-3/4" hole 512-1500'. Ran shoe, 1 jt. 7" 20# J-55, ST&C casing, FC, 32 jts. 7" 20# J-55 ST&C casing, set @ 1377.72', FC @ 1334.55', cemented w/150 sx Class "G" cement w/2% CaCl₂. Plug down @ 11:00 p.m. 7-8-84.
- 7/10-8/13/84 Drilled plug, cement & shoe & washed 1231' to bottom (1500'). Drilled 6¼" hole 1500-5720' (TD).
- 8/13-8/14/84 Ran DIL-Sonic-LDT-CNL-GR logs.
- 8/14-8/16/84 Spotted 45 sx Class "G" w/3% CaCl₂ plug 1424-1300'. WOC. Tagged cement. Soft cement 1330-1389'. Firm cement 1389-1424'. Circulated out contaminated cement. Spotted 50 sx Class "G" w/3% CaCl₂ plug 1389-1139'. WOC. Tagged cement @ 1153'. Spotted 10 sx cement in top of surface casing. Cut off surface pipe 4' below ground level.