

341 So. ...  
Brentwood, Ore.

DEPARTMENT OF GEOLOGY AND MINERAL INDUSTRIES  
State Office Building, Portland 1, Oregon

APPLICATION FOR PERMIT TO DRILL NEW WELL OR STRATIGRAPHIC HOLE  
(To be accompanied by a \$25.00 permit fee for new wells only and a surety bond conditioned as provided by law.)

Vale, Oregon, March 12 1954

Department of Geology and Mineral Industries  
Portland, Oregon

In compliance with rules and regulations pursuant to ORS 520 (Chapter 667 OL 1953) application is hereby made for permit to drill

a (new well) to be known as: Roderick A. Stamey George B. Russell  
(stratigraphic hole)

Well No. one in \_\_\_\_\_ of Sec. 14, T. 19S, R. 44E W. B. & M.,  
Field, Malheur County.

This well is 330 feet (N) (S) of the north line and 330 feet  
(E) (W) of the west line of Section 14, T19S, R44E.

(Give location from section or other legal subdivision lines or corners. Cross out wrong directions)


Elevation of ground above sea level is \_\_\_\_\_ feet. All depth measurements are taken from  
top of derrick floor, which is 5 feet above ground.

The lessee is Roderick A. Stamey

Address 311 Rusk Building, Houston, Texas.

The lessor is George B. Russell

Address Rt. #1, Vale, Oregon



Section of land  
Area 640 acres

LOCATE WELL CORRECTLY

We estimate that the first productive oil or gas sand should occur at a depth of about 2300 feet.  
We propose to use the following strings of casing and to land or cement them as herein indicated:

| Size of hole | Size of casing | Weight in pounds per foot | Grade and type  | New or second hand | Depth   | Landed or cemented No. sacks cement |
|--------------|----------------|---------------------------|-----------------|--------------------|---------|-------------------------------------|
| 8 1/4 "      | 10 3/4 O. D.   | 32.75                     | seamless casing | new                | 200 ft. | 50 sacks of cement                  |
|              |                |                           |                 |                    |         |                                     |
|              |                |                           |                 |                    |         |                                     |
|              |                |                           |                 |                    |         |                                     |

We propose to drill with rotary tools  
~~cable~~

If changes in the above plan become advisable we will notify you before cementing or landing casing.

Additional information including names of and expected depths to objective sands (Use additional sheets as needed):

**The well location is in the northwest corner of the southwest quarter of the northwest quarter of section fourteen.**

I understand that this plan of work must receive approval in writing by the Director of the State Department of Geology and Mineral Industries.

Approved March 26, 1954  
except as follows

DEPARTMENT OF GEOLOGY & MINERAL INDUSTRIES  
By F. W. Liberty Director

Roderick A. Stamey  
Roderick A. Stamey  
CONTRACTOR OPERATOR

By \_\_\_\_\_  
Position \_\_\_\_\_

Send communications regarding well to:  
Name Roderick A. Stamey  
Address 311 Rusk Building  
Houston, Texas