

### HISTORY OF OIL OR GAS WELL

(Submit in duplicate)

In compliance with rules and regulations adopted pursuant to ORS 520.095 (Chapter 667 OL 1953)

Operator REICHHOLD ENERGY CORP.

Field St. Louis

Well No. Werner 14-21

, Sec. 21

, T. 5 N

R. 2 W

W. B. & M.

Date October 28, 1982

Signed *Tim Williamson*

Title Drilling Superintendent

(President, Secretary or Agent)

It is of the greatest importance to have a complete history of the well. Use this form in reporting the history of all important operations at the well, together with the dates thereof, prior to the first production. Include in your report such information as size of hole drilled to cementing or landing depth of casings, number of sacks of cement used in the plugging, number of sacks or number of feet of cement drilled out of casing, depth at which cement plugs started, and depth at which hard cement encountered. If the well was dynamited, give date, size, position and number of shots. If plugs or bridges were put in to test for water, state kind of material used, position and results of pumping or bailing.

Date	Description
9-25-82	Drilling 9 7/8" Surface hole, Depth 396'
9-26-82	Drilling 613'
9-27-82	Drilling 980'
9-28-82	Drilling 1200'
9-29-82	T.D. surface hole @ 1263'. Ran 30 JT's 7" pipe to 1206.68' and cemented with 552 sxs of class 1 cement.
9-30-82	Tested B.O.P.'s and drilling
10- 1-82	Drilling 1420'
10- 2-82	Drilling 1837'
10- 3-82	Drilling 2379'
10- 4-82	Drilling 2473'
10- 5-82	Logging with Schlumberger
10- 6-82	Drilling 2494'
10- 7-82	Drilling 2940'
10- 8-82	Drilling 3354'
10- 9-82	T.D. hole @ 3354', logged with Schlumberger. Rigged up Halliburton and set bottom plug from 3090' - 2880' with 59 sxs Class "G" Cement. Set top plug from 1550' - 1023' with 126 sxs Class "G" Cement.
10-10-82	Tagged plug @ 1023' with Bill King witnessing. Released rig 10-10-82

NOTE: Well is now plugged and abandoned